

coharo coatings

DRY TEXTURE



PRODUCT OVERVIEW

Coharo Coatings Dry Texture is a pre-blended, cement-based texture that is used to achieve a traditional textured sand finish over properly prepared substrates.

Dry Texture is made from 100% recycled glass aggregate, which is equal to around 8 litres of waste glass diverted from landfill in every bag. Not only does this provide more repeatable consistency, but glass aggregate is also free of “rust staining” materials, meaning no customer call backs.

Dry Texture requires nothing but clean, cool water to be added and is easy to apply – simply trowel and float.

Pure white cement can be coloured.

FEATURES AND BENEFITS

- Pre-blended - just add water
- Made from 100% recycled glass aggregate
- Excellent crack resistance
- Ready to paint or seal
- Exceptional workability

SPECIFICATIONS

TYPICAL SYSTEMS	Coharo Coatings Dry Texture is designed for use in 1mm - 2mm applications over any suitable surface which has been prepared correctly following Casafico's Coharo Coatings Systems Guide*
PREPARATION	Substrate must be clean, sound and free of all powdery residues, oils and release agents. Any crumbling, loose or damaged material must be removed. Pre-painted surfaces must have all loose material removed with a wire brush.
MIXING	Add approximately 4L of water, depending on consistency desired. Mix using a slow speed drill with a suitable paddle. Mix until lump free.
APPLICATION PROCEDURE & EQUIPMENT	<ul style="list-style-type: none"> • Apply using a trowel onto prepared substrate (we recommend Coharo Coatings Levelling Coat, Smooth Coat or Patch Adhesive) • Once applied, Dry Texture can be floated to achieve a textured finish • Care should be taken in preparation of the area; areas not to be coated should be carefully masked and protected as material can be difficult to remove if allowed to fully dry

SPECIFICATIONS

CURING TIME	Dry Texture will cure in 1 day depending on thickness applied and substrate. Dry Texture must be cured before applying paint.
COVERAGE PER BAG	10-12m ²
PACKAGING	Dry Texture is supplied in 12 litre/ 19kg paper bags with 42 bags to a pallet. Bags are made to be recycled - make sure to dispose of thoughtfully in recycle commingled to reduce waste to landfill.
CLEAN UP	Clean up with water before it dries
STORAGE & SHELF LIFE	12 months shelf life if stored correctly off the ground in a dry place

PRECAUTIONS AND LIMITATIONS

- Silicone or oil contaminated surfaces are not suitable for rendering
- Not designed for application to sealed or glazed surfaces (Glazed Bricks, Tiles, Glass etc)
- Protect from frosts or rain for the first 8 hours
- Do not apply below 5°C or above 30°C
- *The provision of expansion joints at 'weak spots' ie:
 - Above and below openings
 - At all level changes
 - At the junction of different substrates
 - As specified by the project engineer
- Users must make their own determination as to the suitability of this product relevant to requirement

**Control joints are ultimately the builders responsibility.*

The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.

For all Casafico products technical assistance call 1300 COHARO