

CONATO coatings **LUSTRO WAX**



PRODUCT OVERVIEW

Coharo Coatings Lustro Wax is formulated to a creamy consistency of pharmaceutical grade bees wax that can be used as a protective sealer over Coharo Coatings products such as Concrete Finish, London Finish and Marble Finish.

Lustro Wax leaves a clear, subtle sheen over the finished coating, and is water resistant. It can be applied with a flexible marble finish trowel onto the surface and finished with an absorbent sponge or a lint-free cloth.

Lustro Wax is completely non-toxic and the perfect choice for increased water repellency while leaving a natural look of the finish applied.

FEATURES AND BENEFITS

- Ready to use
- Increased water repellency
- Penetrative for more effective protection
- Does not change the look of the coating
- Easy to use
- Protects coating for longer

SPECIFICATIONS	
TYPICAL SYSTEMS	Coharo Coatings Lustro Wax is designed for application over the following Coharo Coatings products: Concrete Finish London Finish Marble Finish And also a product modifier by adding 500ml to a bag of Concrete Finish or London Finish to enhance application and water resistance
PREPARATION	Finished coating must be cured for 7 days prior to the application of Lustro Wax. Ensure the surface is sound and clean before application commences.
MIXING	No mixing required
APPLICATION PROCEDURE & EQUIPMENT	Apply Lustro Wax with a thin blade flexible trowel in a tight coat and finish with an absorbent sponge or lint free cloth, ensure any excess wax is wiped off

SPECIFICATIONS	
CURING TIME	Lustro Wax is touch dry immediately once excess is removed. Full cure takes approximately 24 hours.
COVERAGE PER PAIL	17m² over Concrete Finish/Litre 60m² over London Finish/Litre 150m² over Marble Finish/Litre
PACKAGING	Lustro Wax is supplied in 1 litre tubs
CLEAN UP	Clean up with a clean dry cloth
STORAGE & SHELF LIFE	36 months shelf life in original/unsealed container

PRECAUTIONS AND LIMITATIONS

- Users must make their own determination as to the suitability of this product relevant to requirement
- Samples should be made prior to use

*Control joints are ultimately the builders responsibility.

The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.