

coharo coatings **PATCH ADHESIVE**



PRODUCT OVERVIEW

Coharo Coatings Patch Adhesive is a pre-blended, polymer modified adhesive base coat that can be used to prepare difficult substrates, set joints and act as an adhesive for Casafico Tecoblock and Polystat Panels.

Patch Adhesive is made from 100% recycled glass aggregate and can be applied up to 1.5mm thick. It is ideal to be used as a base preparation product, creating a sound surface to apply a range of finishes over the top.

FEATURES AND BENEFITS

- Pre-blended - just add water
- Made from 100% recycled glass aggregate
- Excellent shrink resistance
- High polymer for outstanding adhesion
- Easy to apply
- Exceptional workability

SPECIFICATIONS

<p>TYPICAL SYSTEMS</p>	<p>Coharo Coatings Patch Adhesive is designed for use in 1mm - 1.5mm application layers on the following substrates:</p> <ul style="list-style-type: none"> ● Coharo Coatings Levelling Coat ● Plasterboard ● Blueboard ● Fibre cement sheet ● Off-form concrete ● Tecoblock ● Polystat Panel
<p>PREPARATION</p>	<p>Substrate must be clean, sound and free of all powdery residues, oils and release agents. Any crumbling, loose or damaged material must be removed. Pre-painted surfaces must have all loose material removed with a wire brush.</p>
<p>MIXING</p>	<p>Add approximately 4L of water, depending on consistency desired. Mix using a slow speed drill with a suitable paddle. Mix until lump free.</p>

SPECIFICATIONS

APPLICATION PROCEDURE & EQUIPMENT	<ul style="list-style-type: none">● Apply using a hawk and trowel or spray machine● When coating is stabilised, Patch Adhesive can be flattened via trowel or sponge finished
CURING TIME	Patch Adhesive will set in 1 - 4 hours depending on substrate moisture and thickness applied. Allow 1 day before coating with a different product.
COVERAGE PER BAG	1mm thickness - 10m ² per coat, per bag
PACKAGING	Patch Adhesive is supplied in 12 litre/ 15kg paper bags with 60 bags to a pallet. Bags are made to be recycled - make sure to dispose of thoughtfully in recycle commingled to reduce waste to landfill.
CLEAN UP	Clean up with water before it dries
STORAGE & SHELF LIFE	12 months shelf life if stored correctly off the ground in a dry place

PRECAUTIONS AND LIMITATIONS

- Silicone or oil contaminated surfaces are not suitable for rendering
- Protect from frosts or rain for the first 8 hours
- Do not apply below 5°C or above 30°C
- *The provision of expansion joints at 'weak spots' ie:
 - Above and below openings
 - At all level changes
 - At the junction of different substrates
 - As specified by the project engineer
- Users must make their own determination as to the suitability of this product relevant to requirement

**Control joints are ultimately the builders responsibility.*

The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.

For all Casafico products technical assistance call 1300 COHARO