

coharo coatings

PURO FINISH



PRODUCT OVERVIEW

Coharo Coatings Puro Finish is inspired by the earthy and romantic country-style of Tuscany. Puro Finish allows you to achieve the rustic yet elegant aged look instantly and easily. Puro Finish is available in fine and course grades which will 'age' with weathering.

Inspired by the hills of Italy, Puro Finish comes in a range of beautiful colours which are soft and warm, such as soft terracotta, earthy ochre, dusty greens and creamy clay-like creams and greys

Made using quality recycled glass, you can feel good knowing that you have made the best choice for your clients and the environment.

FEATURES AND BENEFITS

- Pre-blended - just add water
- Made from 100% recycled glass aggregate
- Excellent crack resistance
- Available in a range of beautiful colours
- Exceptional workability
- Easy to use

SPECIFICATIONS

TYPICAL SYSTEMS	Coharo Coatings Puro Finish is designed for use in 1mm application layers over any suitable surface which has been prepared correctly following Casafico Coharo Systems Guide
PREPARATION	Substrate must be clean, sound and free of all powdery residues, oils and release agents. Any crumbling, loose or damaged material must be removed. Pre-painted surfaces must have all loose material removed with a wire brush. Coharo Coatings base preparation products must be used in accordance with our recommendations.
MIXING	Add approximately 3L of water to a 15L pail and pour bag contents into the bucket, depending on consistency desired. Mix using a slow speed drill with a suitable paddle. Mix until lump free.

SPECIFICATIONS

APPLICATION PROCEDURE & EQUIPMENT	<ul style="list-style-type: none">● Apply using a trowel onto prepared substrate (we recommend Coharo Coatings Smooth Coat or Patch Adhesive)● Once applied, Puro Finish can be sponged to achieve a fine textured finish● Puro Finish must be cured before applying Puro Seal or paint<ul style="list-style-type: none">○ Puro Finish requires 2 coats over prepared base● Care should be taken in preparation of the area; areas not to be coated should be carefully masked and protected as material can be difficult to remove if allowed to fully dry
CURING TIME	1 day
COVERAGE PER PAIL	Puro Finish Fine - 7m ² coverage (2 coat application)
PACKAGING	Puro Finish is supplied in 15 litre/20kg pails
CLEAN UP	Clean up with water before it dries
STORAGE & SHELF LIFE	12 months shelf life in original/unsealed container

PRECAUTIONS AND LIMITATIONS

- Silicone or oil contaminated surfaces are not suitable for rendering
- Not designed for application to sealed or glazed surfaces (Glazed Bricks, Tiles, Glass etc)
- Protect from frosts or rain for the first 8 hours
- Do not apply below 5°C or above 30°C
- *The provision of expansion joints at 'weak spots' ie:
 - Above and below openings
 - At all level changes
 - At the junction of different substrates
 - As specified by the project engineer
- Users must make their own determination as to the suitability of this product relevant to requirement

**Control joints are ultimately the builders responsibility.*

The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.

For all Casafico products technical assistance call 1300 COHARO